



## OL-70V-6

TruAudio's Commercial Surface-Mount Outdoor Speaker is equipped with 70v and 100v tap settings to easily create a distributed audio system throughout a commercial space. A high-excursion 6.5" polypropylene woofer provides low bass extension, and the 1" soft dome tweeter provides accurate clarity over a wide area.

The IP66 rating provides environmental endurance and protection from outdoor elements. Featuring a weatherproof, extreme temperature resistant cabinet and corrosion-proof aluminum grill, making it a perfect fit for any outdoor application.

Low-profile mounting bracket allows for vertical or horizontal 120 degree range of motion.

Available in either black or white finishes.



Vertical or Horizontal  
Mounting Options

### OL-70v-6WT/BK

|                          |   |
|--------------------------|---|
| <b>Speaker Type:</b>     | Outdoor, 2 way 70v                                    |
| <b>Woofers:</b>          | 6.5" polypropylene                                    |
| <b>Tweeter:</b>          | 1" silk   |
| <b>Power:</b>            | 30 watts  |
| <b>Impedance:</b>        | 70v/100v  |
| <b>70v Taps:</b>         | 2W - 15W selectable                                   |
| <b>100v Taps:</b>        | 4W - 30W selectable                                   |
| <b>Freq Response:</b>    | 55 - 20k Hz (+/-3 dB)                                 |
| <b>Sensitivity:</b>      | 86 dB   |
| <b>Grill Type:</b>       | Aluminum mesh   |
| <b>Colors Available:</b> | Black, white  |
| <b>Mounting:</b>         | U bracket   |
| <b>Cabinet Size:</b>     | 11.9" (303mm) H,<br>8.5" (215mm) W,<br>7.5" (191mm) D |

Family:



UNIVERSAL

